



DCN692N-XJ

Spikpistol, 18 V, XR, Li-Ion, 5,0 Ah, 2 hastigheter, utan batterier

Säljargument

- Cordless design allows you to work without the inconvenience and safety risk of trailing lead
- Two speeds - or power levels - to optimise the nailer for firing all lengths of nails
- The sequential operating mode allows for precision placement and the bump operating mode provides the user with production speed
- Reversible belt/rafter hook provides increased portability and versatility on the job-site
- Benefit from longer runtime, quicker readiness to fire, less recoil and more durability when firing short nails
- Tool free stall/jam clearance minimises user down time
- Ergonomic tool design allows the nailer to fit easily between a 400mm centre stud
- User can engage contact trip lock-off and prevent accidental dis-charge of fastener
- Versatile 30 - 34 degree magazine angle will accept most clipped head, and off centre round head paper tape or wire weld collated framing nails
- 18V XR Li-Ion Two Speed Framing Nailer featuring BRUSHLESS motor technology and XR 5.0Ah battery packs
- BRUSHLESS motor technology offers the power to fire a 90mm Ring Shank nail in Soft Wood and 63mm into Hard Woods
- Depths can be easily adjusted using the thumb wheel depth adjuster
- Increased visibility and durability along with protection for work-surface from the non-mar contact-trip
- Mechanical rather than gas operation offers consistent performance at temperature between -20 and 50 degrees Celsius and minimal cleaning/service requirements
- Gas free operation offers a significant saving in running costs
- Class leading vibration and sound figures, offer fantastic user protection
- Dry fire lockout ensures that the tool is protected from firing without nails in the magazine

Standardutrustning

- bälteskrok för valfri sida
- extra skydd för kontaktnosen

Garanti

- DEWALT 1-års garanti på elverktyg

Specifikationer	
Klammerlängd	50-90 mm
Spik-/dyckertdiameter	2.8-3.3 mm
Magasinsvinkel	30-34 °
Avfyrnings-/manövreringsläge	Stöt och sekventiell
Magasinskapacitet	55 spik
Strömkälla	Batteridrivnen
Batteri	Li-Ion
Bandningstyp	Pinne
Bredd	125 mm
Höjd	338 mm
Vikt	3.6 kg
Integrerad upphängningskrok	Yes
Enkel rensning av spikstopp	Yes
Buller LpA / KPA, 1 s, d	82/3
Buller LWA / KWA, 1 s, d	93/3
Värde för vibrationsutsläpp ah	2.5 m/s ²
Avvikelse K 1 (vibration)	1.5 m/s ²